

Unlocking Hyperscale Connectivity: The Rise of Managed Optical Fiber Networks (MOFN)

CISCO Live !

Anuj Malik
Director, Product Strategy & Management

 anujmalik

Nanda Divvela
Product Manager

Cisco Webex App


Questions?

Use Cisco Webex App to chat with the speaker after the session

How

- 1 Find this session in the Cisco Live Mobile App
- 2 Click “Join the Discussion”
- 3 Install the Webex App or go directly to the Webex space
- 4 Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until 14 November 2025.



<https://ciscolive.ciscoevents.com/ciscolivebot/#BRKMSI-2224>

Agenda

- 01 What is MOFN ?
- 02 Key Drivers for MOFN
- 03 Types of MOFN
- 04 Cisco MOFN Solutions
- 05 Cisco Coherent Optics
- 06 Cisco Optical Transport


Demystifying MOFN

MOFN – What ChatGPT says?

A **Managed Optical Fiber Network (MOFN)** is a fiber-based connectivity service where the network provider delivers **high-capacity optical links** and **actively manages** the performance, configuration, and maintenance of the network for customers such as hyperscalers, enterprises, and carriers.

The need for connectivity ..

- AI training and inference workloads are driving increases in global data center capacity
 - \$5.2T in data center CapEx expected through 2030¹
 - 3.5x increase in data center capacity demand through 2030¹
- Content and cloud providers now account for more than 70% of international bandwidth, driving the need to connect to data centers at major regional hubs/landing stations²
- Regional data center capacity growth is exploding
 - By 2030, Asia Pacific will have the highest data center capacity and growth: 13.1% increase in capacity to 37.6 gW³
- Critical need for data center interconnects which can be a few kilometers to thousands of kilometers apart.
 - From landing stations to inland data centers
 - Between regional training data centers and enterprise data sources



KPMG The Asia Data Centre Landscape:
<https://assets.kpmg.com/content/dam/kpmg/cn/pdf/en/2025/03/the-asia-data-centre-landscape.pdf>

Capacity Service Options by Service Providers

Dark Fiber

- Fiber lease or IRU
- Fiber Route Diversity
- Colocation and/or Hut facilities
- End customer has full control to engineer network
- OTDR monitoring



COLO/ILA-huts

External Fiber Plant

Wavelengths

- 1G/10G/100G/400G/800G
- Protected, unprotected
- Latency SLAs
- Proactive monitoring and repair



CPE



Central Office



External Fiber Plant

Managed Spectrum

- N x 12.5GHz
- Faster turn-up, lower cost and opex compared to dark fiber
- Guard Band applied to protect other services
- Spectrum Power Monitoring



COLO/POP



External Fiber Plant

MOFN

- Managed Network including Fiber at SLA specified
- Product/Architecture can be specified by end customer
- Proactive monitoring and repair




COLO/DC



External Fiber Plant

Managed Optical Fiber Networks (MOFNs)

- Key Drivers:
 - Web/Hyperscale operators cannot own/lease dark fiber without a telecom license in certain geographies
 - Faster TTM vs procuring fiber and managing network directly
- Local carriers to build and manage optical transport networks for end customer using technologies/products they prefer.



Why MOFNs are Win-Win for Hyperscalers & Service Providers ?

Hyperscalers

Faster time to market

Scale

Customization



Service Providers


Incremental Revenue

Partnership

MOFN Solutions


Architectures choices for MOFN

Traditional Architecture



Demarcation between IP and Optical


RON Architecture



Much Lower Total Cost of Ownership (TCO)

Significantly reduce capital and operating expenses
by 50% or more

How to operate a MOFN network ?



Cisco MOFN Solution Building blocks...

Cisco Routing Platforms: 8000, NCS, and ASR


Unparalleled performance, TCO, and operational simplicity



IP & Optical Automation & Assurance


Vendor Agnostic Hierarchical Control

Visualization, Assurance and Provisioning of both IP and Optical domains



Cisco Coherent Pluggables & Optical Transport

Comprehensive lineup of coherent optics and optical transport platforms



Cisco or 3rd Party Open Line Systems (OLS)

Full featured OLS with mesh ROADMs and in-line amplification




**MOFN
Solution**

Cisco Optical Innovations & Coherent Pluggables

Market/Technology Trends – Coherent Pluggables

Coherent Pluggables % Continue Increasing

- Today coherent ports are dominated by pluggables
- IP-over-DWDM gaining widespread adoption



Coherent Pluggables Expanding Applications


Farther: 400G ULH




Wider: L-Band



Shorter: Coherent Lite



800G Coherent Market Takes Shape



Acacia/Cisco continues to be the pioneer in coherent pluggables: 800G ZR+ (interop PCS), 400G ULH

Coherent Pluggable Brings Some Important Levers



01

Network costs and efficiencies

CapEx cost breakdown, \$/100G, PAYG models, etc.

02

Power, thermal, and space

Compact devices, Watt/100G, DC power and rack space optimization

03

Network architectures


Disaggregation, optimize topologies, spectrum efficiency

04


Drives interoperability

MSAs/standards, best in breed adoption

Acacia Coherent Technology Innovation



Vertical Integration is Key to Lowest Cost and Best Performance



Cisco is the only company that is 100% Vertically Integrated today

Approaches of Coherent Implementation



MSA
Pluggable
(aka DCO)



Industry's first pluggable coherent module (100G CFP)



100G/200G CFP2-DCO




400G pluggable portfolio in QSFP-DD, OSFP and CFP2



800ZR/ZR+ and 400G ULH pluggables - QSFP-DD & OSFP

Deployed in router/switches and transport platforms (e.g., 8K, ASR9K, NCS, Nexus 9K etc.)

Performance
Optimized



400G multi-haul module (AC400)



1.2T Coherent Module (AC1200)




Industry's first 1.2T coherent multi-haul pluggable (CIM8)

Deployed in transport platforms (e.g., NCS 1004, 1014 etc.)


400G QSFP-DD Digital Coherent Optics Portfolio

ER1




Point to Point

Intra-data center, campus interconnect, core-to-edge router



Lowest Cost

Based on fixed laser with simple point-to-point connectivity



Short Reach

Up to 45KM for unamplified at 13dB

Use Case %




Network Coverage

ZR




Point to Point

Web, Data Center Interconnect, Non-SP/SP router interconnect



Low Cost

Lowest cost 400G DCO option for very simple designs



Short Reach


Up to 120KM for P2P amplified links

Use Case %



Network Coverage

Bright ZR+



Transport Centric

WebService Providers, Routed Optical Networking



High TX Power

+1dbm for difficult spans; interop with brownfield transponder & legacy line systems



Advanced Features

TOF, OTN and L1 Encryption features; integrated optical amplifier

Use Case %



Network Coverage

400G ULH



Transport Centric

Service Providers, Routed Optical Networking



Long Haul Optimized

400G with **RON Anywhere** up to 3000km, high Tx power



Power Optimized






Designed to fit in all routers support 400G Bright ZR+ today

Use Case %



Network Coverage

Expanding Pluggables to Access & Long-Haul networks ..



Cisco 400G Ultra Long-Haul (ULH) Module

GA

400G High Performance module suitable for regional, long haul and subsea use cases

Designed for existing host platforms with same electrical interface (8x56G SerDes) and power <24W

Feature rich – integrated amplifier & TOF (Tx power +1dBm), C & L band variants, CMIS 5.3 compliant




Cisco 400G QSFP-DD ULH
(DP04QSDD-ULH-A1)

400G 16QAM PCS
(66/75/87/98GBd)

400G QPSK
(OpenROADM)


400G 16QAM
(OpenZR+)



400ULH: Successful Field Trials*


AARNet: 4,600km Link

- Sydney-Perth Indigo Central subsea cable
- 75Gbaud transmission



GÉANT: 3403km Link

- London → Paris → Geneva → Frankfurt → Amsterdam → London
- Multiple spans, 7 ROADMs, 42 amplifier sites, 3rd party OLS
- 118GBaud, 150GHz spacing




Internet2: 3000km Link

- Albany-Indianapolis
- Multiple spans, multiple ROADMs, 3rd party OLS
- 118GBaud, 137.5GHz spacing




Arelion: 2250km Link

- Denver-Chicago
- Mix of G.652 and G.655, multiple ROADMs, 3rd party OLS
- 98Gbaud, 112.5GHz spacing



800G Coherent Pluggables

GA



800G ZR+ Successful Field Trials

Colt: First Ever 800G ZR+ Field Trial


- Frankfurt-Munich, 634km w/ margin
- Mix of G.652 and G.655 w/ multiple >100km spans, multiple ROADMs



Arelion: First >1000km 800G ZR+ Field Trial

- Stockholm-Hamburg, 1069km w/ margin
- Multiple >100km spans, multiple ROADMs


*Arelion



- Trials used Acacia/Cisco 800G ZR+ QSFP-DD coherent pluggable modules (DCOs)
- Leverages industry standard enhanced performance OpenROADM interoperable PCS mode

100ZR QSFP28 Coherent Pluggable

Designed for Access, Aggregation,
Metro, X-haul, and Campus
Interconnect



Cisco QSFP28 100G ZR
(DP01QS28-E20/E25)

Gen 1

- P2P unamplified reach: 80KM
- Amplified reach: 300KM
- Tx power: -8dBm
- Max power <5.5W

Gen 2

- P2P unamplified reach: 140KM
- Amplified reach: 500KM
- Tx power: 0dBm
- Max power <6W

GA

iTemp variant available for deployment in outdoor plants and environment


First Pluggable to Break into the Terabit Era

Coherent Interconnect Module 8 (CIM 8) powered by Jannu DSP

20%+ performance with 3D shaping – 800G covers 90% of network

65% lower power than competition

3D Siliconization packaging



2.4Tbps Transponder



NCS 1014 Next-Gen compact modular shelf



Single carrier 140Gbd 1.2T faceplate pluggable

Top Networks Are Adopting Our Technology

NCS 1014 Industry Leading Performance

verizon✓



Commercial fiber network with 1Tbps across 14x spans



windstream wholesale



1 Tbps wavelength over a 1,100 km link across Windstream's Intelligent Converged Optical Network



800Gbps on the Amitié transatlantic communications cable




Longest distance 400 Gbps transmission trial on the Indigo subsea cable system; 18,400 km from Sydney to Singapore

Cisco Optical Transport

MOFN Optical Transport Solution Offerings

Solution #1: 1.2T CIM8 Module


NCS 1014 2.4T Transponders with NCS 1001 Line Systems
Managed by Cisco Optical Network Controller



- 9.6T in 2RU
- 32x1.2T, 38.4T/fiber pair best capacity (C band)
- 4 x NCS1014 per fiber pair

Solution #2: 400ZR/ZR+ Coherent Pluggables

NCS 1014 3.2T Transponders with 400ZR optics and Cisco or 3rd party OLS
Managed by Cisco Optical Network Controller



- 12.8T in 2RU
- 64x400G, 25.6T/FP (C band), 2 x NCS1014 per FP
- Highest density
- Low power consumption

NCS 1014 Optical Transport Solution

3.2T QXP with 400G Coherent

2.4T TXP with CIM8




- 400ZR, 400ZRP, 400G-ULH*
- 100GE, 400GE
- Wire-speed Line Encryption*
- C-Band, L-Band support*
- 8x TXP/MXP/Regen* per card – 32x per shelf
- In-built PRBS testing
- QDD-OLS, QDD-OTDR*, QDD-PSM* plugs supported

- 140GBd 1.2T
- 100GE, 400GE, 800GE
- Wire-speed Line Encryption
- C & L-Band support
- Subsea extended CD support, NLEQ support
- Fast SOP tracking for aerial fibers
- In-built client and trunk PRBS testing

Metro-DCI Line Systems



QDD-OLS



NCS 1001 with MD64



NCS 1014 DCI-OLS with MD32

- Compact
- Built-in OTDR, OCM (NCS 1001, 1014)
- Built-in Coherent Probe and equalization (NCS 1014)
- Different fixed add-drop option – MD32, MD64
- PSM protection (NCS 1001, NCS 1014*)
- QDD-OLS for low-capacity use cases
- NCS 1014 allows TXPs and OLS to be combined in one shelf

Cisco NCS 1010 C+L Line System

Enhanced Visibility and control

- Equalization Everywhere
- Optical Channel Monitoring (OCM) everywhere
- OTDR everywhere
- ASE loading

Automation First

- ZTP for device turn-up
- Automated E2E link turn-up
- Streaming telemetry

Multi-purpose

- Open Line System
- Spectrum Service Ready
- Terrestrial & SLTE
- HCF ready

Simple & Integrated design

- One degree / ILA per shelf
- Better MTBF
- Easier to deploy




NCS 1010

C+L Long Haul Open Line System

NCS 1014 CIM 8 Delivers 64T for C+L Long Haul

64T (32T in C-Band and 32T in L-Band) with NCS 1014 and Coherent Interconnect Module 8 over NCS 1010 C+L Open Line Systems and *Corning Vascade EX2500* fiber




MOFN Optical Transport Protection Options



Optical Protection Options for different customer use cases


- **Optical Channel Protection (with or without restoration)** – mainly used in Long Haul
- **Optical Multiplex Section Protection** – 2-way, 3-way, 4-way – used in metro
- **Optical Transport Section Protection** – 2-way for span protection in Long Haul
- **Client Protection** – E2E protection required by some enterprise customers.



Cisco Optical Site Manager (COSM)

- COSM is a Web UI for NCS1K/2K
 - Run in NCS1K RCP embedded SW (XR) or
 - Run in NCS2K SVO-LC (up to 15 COSM per SVO Controller)
- Rack/Chassis/Module mechanical View
- Visualize Alarms (on chassis/card/port)
- Alarms & events table – Current & History
- Visualize physical and logical Inventory
- Card Mode Configuration wizard (steppers)
- PM Live & Last 32 bins
- PRBS, Loopbacks
- TCA & Alarm profile settings
- SW Database , Upgrade Backup & Restore
- Netconf/YANG NBI


Chassis front/back View




Card View




Rack View



OTDR




Optical Channel Monitoring



Card – alarms, events

Card Mode Configuration




PM – last 32 intervals


Live PM | PRBS | Loopbacks




Node View



Degree View



Component View



Cisco Optical Network Controller (CONC)

CONC is web-UI, Microservices K8s software
NCS 1000 and NCS 2000 – available on 25.x

Telemetry & KPI

OUTCOME: Reduce time to identify anomalies, time to act

Configuration/Provisioning



OUTCOME: Reduce time to monetize, Eliminate errors in provisioning, TAPI or REST NBIs for multi-later orchestration

Fault Management


OUTCOME Reduce time to identify anomaly, time to restore services, time to plan maintenance/growth

Inventory and Topology Management


OUTCOME Know your network, simplify operations



Network: Topology view



Network: Circuit view



Site view

Node Functional View

Rack/Chassis/Card View

Node Functional View

View

Alarms/OTDR/OC

Alarms

Fetches at: 04/14/2023, 12:41:43

Rack	UID	Device Name	Severity	Service ...	Condition	Timestamp
			Warning	NSA	USER-LOGOUT	04/14/2023, 12:2
			Warning	NSA	USER-LOGIN	04/14/2023, 12:2
			Warning	NSA	LOGIN-FAILURE-PSWD	04/14/2023, 07:5
			Minor	NSA	PROTNA	04/11/2023, 13:1

OAM

defaultNode

Side List

Degree 1

OTDR

Degree 2

OTDR

OXF List (1)

mcs1010_OCH

Frequency: 195.9 THz

Wdm: 75 nm


Wavelength: 1930.33 THz

© 2025 Cisco and/or its affiliates. All rights reserved.

BRKMSI-2224

MOFN Optical Transport Network Planning & Design

Cisco Optical Network Planner: The Next generation Multi-layer Design and Planning tool from Cisco



Summary

Market Momentum

Explosive growth in AI, DCI traffic; hyperscalers are turning to managed models for scalability and speed of deployment.

MOFN is Win-Win

MOFN delivers scalable, and reliable optical transport to hyperscalers while offloading operational complexities.

Cisco Advantage

End-to-end solution: optics, automation, management, and support with 100% vertical integration

Complete your session evaluations



Complete a minimum of 4 session surveys and the Overall Event Survey to claim a Cisco Live T-Shirt.



Earn up to 800 points by completing all surveys and climb the Cisco Live Challenge leaderboard.



Level up and earn exclusive prizes!



Complete your surveys in the Cisco Live Events app.

Continue your education



Visit the Cisco Stand for related demos



Book your one-on-one Meet the Expert meeting



Attend the interactive education with Capture the Flag, and Walk-in Labs



Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand

Thank you

CISCO Live !

